

*DYNAMIC
INSTRUMENTS*

CallSAFE™ *for Reliant*

SECURE ONLINE STORAGE - RAID 5 DISK ARRAY SYSTEM

CallSAFE™ is a complete audio storage and management system providing long-term audio and data retention. Use our robust search engine to locate events, lock critical calls from automatic purging and classify by call type and content from both local and remote workstations.



CallSAFE™ *for Reliant*

The multi-tier security system thwarts unwanted access. Call data is safe guarded on a fault-tolerant, disk array system and critical components can be replaced while the system continues to operate without performance impact.



Long-term call storage deserves ...

CallSAFE™ *for Reliant*

Record Locate Retrieve Duplicate Distribute

Executive Communication Systems • (800)/(805) 644-9525, ext. 103 • www.PSAPLogging.com • sales@PSAPLogging.com

- **Extensive Online Call Storage**
- **Local and Remote Call Access**
- **Intelligent Search Engine**
- **Call Type Classification**
- **Retains most recent Call Data**
- **Protect Critical Calls from Purging**
- **RAID 5 Data Storage**
- **Fault Tolerant System Operation**
- **Redundant – Power Supplies, Hard Rives and Fans**
- **Hot Standby RAID Drive**
- **Automatic Drive Recovery**

Tools NOT Toys!



CallSAFE™

for Reliant

SECURE ONLINE STORAGE - RAID 5 DISK ARRAY SYSTEM

CHASSIS

CAPACITY	F1	F3	F4
320 GB	X		
480 GB	X	X	
640 GB	X	X	
800 GB		X	
960 GB		X	X
1120 GB		X	X
1280 GB		X	X
1440 GB		X	X
1600 GB		X	X
1760 GB			X
1920 GB			X
2080 GB			X
2240 GB			X

- ★ **Extended online storage** – Locate calls from months past without handling media discs or leaving the convenience of your workspace environment.
- ★ **Redundant & secure data storage** – Critical system components operate in a mirrored architecture and can be replaced without impacting system operations.
- ★ **Unattended operation** — Fashion a completely hands free voice logging system, operating from your phone or equipment room and with desktop access to all stored calls.

CallSAFE™ for Reliant Specifications*

DESCRIPTION	F1	F3	F4
Available Configuration	Rackmount	Rackmount	Rackmount
Power Supply Capacity	Dual 250 Watt	Dual 450 Watt	3 X 320 Watt
Relative Humidity	Redundant	Redundant	Redundant
AC Input Voltage	10% to 85%	10% to 85%	10% to 85%
Operating Temperature	Non-condensing	Non-condensing	Non-condensing
Non-operating Temperature	110/220V (+/- 10%)	110/220V (+/- 10%)	110/220V (+/- 10%)
	60/50 Hz	60/50 Hz	60/50 Hz
	5°C – 40°C	5°C – 40°C	5°C – 40°C
	-25° – 60°C	-25° – 60°C	-25° – 60°C

* Specifications subject to change without notice.

